

Diethyl ether ≥99.5 % for synthesis, stabilized

article number: **5920** Version: **3.0 en** Replaces version of: 02.04.2020 Version: (2)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance	Diethyl ether ≥99.5 % for synthesis, stabilized
Article number	5920
Registration number (REACH)	01-2119535785-29-xxxx
Index number in CLP Annex VI	603-022-00-4
EC number	200-467-2
CAS number	60-29-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Laboratory chemical Laboratory and analytical use

Uses advised against:

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	2.6 Flammable liquid		Flam. Liq. 1	H224
3.10	10 Acute toxicity (oral)		Acute Tox. 4	H302
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

date of compilation: 07.12.2015 Revision: 20.05.2022

according to Regulation (EC) No. 1907/2006 (REACH)

Diethyl ether ≥99.5 % for synthesis, stabilized



article number: 5920

Suppleme	ental hazard information	
Code	Supplemental hazard information	
EUH019	UH019 may form explosive peroxides	
EUH066	repeated exposure may cause skin dryness or cracking	

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal	word	Danger
Siynai	woru	Danyei

Pictograms

GHS02, GHS07



Hazard statements

H224	Extremely flammable liquid and vapour
H302	Harmful if swallowed
H336	May cause drowsiness or dizziness

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking
P243	Take action to prevent static discharges
P261	Avoid breathing dust/fume/gas/mist/vapours/spray

Precautionary statements - response

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water [or shower]
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P312	Call a POISON CENTRE/doctor if you feel unwell

Supplemental hazard information

EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Symbol(s)



H224

Extremely flammable liquid and vapour.

according to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ≥99.5 % for synthesis, stabilized

article number: 5920

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Diethyl ether
Molecular formula	$C_4H_{10}O$
Molar mass	74,12 ^g / _{mol}
REACH Reg. No	01-2119535785-29-xxxx
CAS No	60-29-7
EC No	200-467-2
Index No	603-022-00-4

To stabilise:

Name of substance	Identifier	Wt%
Butylated hydroxytoluene	CAS No 128-37-0	< 0,1
	EC No 204-881-4	

Substance, Specific Conc. Limits, M-factors, ATE			
Specific Conc. Limits M-Factors ATE Exposure rol			
-	-	1.215 ^{mg} / _{kg}	oral

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Diethyl ether ≥99.5 % for synthesis, stabilized



article number: **5920**

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth with water (only if the person is conscious). Call a doctor.

4.2 Most important symptoms and effects, both acute and delayed Irritant effects, Vomiting, Vertigo, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

according to Regulation (EC) No. 1907/2006 (REACH)





article number: 5920

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

humidity, UV-radiation/sunlight, contact with air/oxygen

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

according to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ≥99.5 % for synthesis, stabilized

article number: 5920

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	diethyl ether	60-29-7	IOELV	100	308	200	616				2000/39/ EC
MT	diethyl ether	60-29-7	OELV	100	308	200	616				CAP. 424

Notation

TWA

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

Relevant DN	elevant DNELs and other threshold levels											
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time								
DNEL	308 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects								
DNEL	616 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects								
DNEL	44 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects								

Relevant DNELs of components of the mixture												
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time						
Butylated hydroxy- toluene	128-37-0	DNEL	19 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects						
Butylated hydroxy- toluene	128-37-0	DNEL	18 mg/m ³	human, inhalat- ory	worker (industry)	acute - systemic effects						
Butylated hydroxy- toluene	128-37-0	DNEL	3,5 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects						
Butylated hydroxy- toluene	128-37-0	DNEL	0,5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects						

Environmental values

according to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ≥99.5 % for synthesis, stabilized

article number: 5920

Relevant	Relevant PNECs and other threshold levels										
End- point	Threshold level	Organism	Environmental com- partment	Exposure time							
PNEC	2 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)							
PNEC	0,2 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)							
PNEC	4,2 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)							
PNEC	9,14 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)							
PNEC	0,914 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)							
PNEC	0,66 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)							

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Butylated hydroxy- toluene	128-37-0	PNEC	8,33 ^{mg} / _{kg}	aquatic organ- isms	water	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	1,99 ^{µg} / _l	aquatic organ- isms	water	intermittent re- lease
Butylated hydroxy- toluene	128-37-0	PNEC	0,199 ^{µg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	0,02 ^{µg} / _l	aquatic organ- isms	marine water	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	0,17 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	99,6 ^{µg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	9,96 ^{µg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	47,69 ^{µg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



Diethyl ether ≥99.5 % for synthesis, stabilized



article number: **5920**

hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM (fluoro rubber)

material thickness

0,65 mm

• breakthrough times of the glove material

>30 minutes (permeation: level 2)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	mild sweet
Melting point/freezing point	-116 °C
Boiling point or initial boiling point and boiling range	34,58 – 34,59 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	50 g/m³ (LEL) - 1.100 g/m³ (UEL) / 1,7 vol% (LEL) - 39 vol% (UEL)
Flash point	-40 °C (c.c.)
Auto-ignition temperature	175 °C at 1 atm (ECHA)
Decomposition temperature	not relevant

according to Regulation (EC) No. 1907/2006 (REACH)

Diethyl ether ≥99.5 % for synthesis, stabilized



article number: 5920

	pH (value)	not determined
	Kinematic viscosity	0,331 ^{mm²} / _s at 293,2 K
	Dynamic viscosity	0,235 mPa s at 293,2 K
	Solubility(ies)	
	Water solubility	64,9 ^g / _l at 20 °C (ECHA)
	Partition coefficient	
	Partition coefficient n-octanol/water (log value):	1,19 (pH value: 7, 25 °C) (ECHA)
	Soil organic carbon/water (log KOC)	0,987 (ECHA)
	Vapour pressure	589,6 hPa at 20 °C
	Density and/or relative density	
	Density	0,71 ^g / _{cm³} at 20 °C (ECHA)
	Relative vapour density	2,56 (air = 1)
	Particle characteristics	not relevant (liquid)
	Other safety parameters	
	Oxidising properties	none
2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.
	Other safety characteristics:	
	Gas group (explosion group)	IIB Maximum Experimental Safe Gap value; 0,5 mm MESG ≤ 0,9 mm
	Maximum explosion pressure	9,2 bar
	Temperature class (EU, acc. to ATEX)	T4 Maximum permissible surface temperature on the equipment: 135°C

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air. May form explosive peroxides.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of tem-

according to Regulation (EC) No. 1907/2006 (REACH)

Diethyl ether ≥99.5 % for synthesis, stabilized



article number: 5920

perature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Nitrate, Perchlorates, Peroxides, Nitric acid, Oxygen, Sulphuric acid, Nitrogen oxides (NOx), Hydrogen peroxide, => Explosive properties

10.4 Conditions to avoid

UV-radiation/sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from moisture.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Peroxides.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if swallowed.

Acute toxicity											
Exposure route	Endpoint	Value	Species	Method	Source						
oral	LD50	1.215 ^{mg} / _{kg}	rat		TOXNET						

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Butylated hydroxytoluene	128-37-0	oral	LD50	>6.000 ^{mg} / _{kg}	rat
Butylated hydroxytoluene	128-37-0	dermal	LD50	>2.000 ^{mg} / _{kg}	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

according to Regulation (EC) No. 1907/2006 (REACH)

Diethyl ether ≥99.5 % for synthesis, stabilized



article number: 5920

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting

• If in eyes

Data are not available.

• If inhaled

Inebriation, vertigo, dizziness, fatigue, narcosis

• If on skin

Frequently or prolonged contact with skin may cause dermal irritation, has degreasing effect on the skin, repeated exposure may cause skin dryness or cracking

Other information

Other adverse effects: Circulatory collapse

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)											
Endpoint	Value		Species		Source		Exposure time				
ErC50	>100 ^{mg} / _l		algae			ECHA	72 h				
Aquatic toxicity (acute) of components of the mixture											
Name of sub- stance	CAS No	Endpoint		nt Value		Species	Exposure time				
Butylated hydroxy- toluene	128-37-0	L	250	>0,57 ^{mg} / _l		fish	96 h				
Butylated hydroxy- toluene	128-37-0	EC50		EC50 0,48 ^{mg} / _l		aquatic invertebrates	48 h				
Butylated hydroxy- toluene	128-37-0	Er	C50	>0,4 ^{mg} / _l		algae	72 h				

according to Regulation (EC) No. 1907/2006 (REACH)

Diethyl ether ≥99.5 % for synthesis, stabilized



article number: 5920

Aquatic toxicity (chronic)										
Endpoint	Value	Species	Source	Exposure time						
EC50	>100 ^{mg} / _l	aquatic invertebrates	ECHA	21 d						

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Butylated hydroxy- toluene	128-37-0	EC50	0,096 ^{mg} / _l	aquatic invertebrates	21 d

Biodegradation

Not readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: 2,59 ^{mg}/_{mg} Theoretical Carbon Dioxide: 2,375 ^{mg}/_{mg}

Degradability of components of the mixture							
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source	
Butylated hy- droxytoluene		biotic/abiotic	<10 %	20 d			

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)			1,19 (pH value: 7, 25 °C) (ECHA)				
BCF 2,29							
Bioaccumulative potential of components of the mixture							
Name of substance CAS No BCF Log KOW BOD5/COD							
Butylated hydroxytoluene	128-37-0	598,4	598,4 5,1				

12.4 Mobility in soil

The Organic Carbon normalised adsorption 0, coefficient	0,987 (ECHA)
---	--------------

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties Not listed.

12.7 Other adverse effects

Data are not available.

according to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ≥99.5 % for synthesis, stabilized

article number: 5920

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN number or ID number	
	ADR	UN 1155
	IMDG-Code	UN 1155
	ICAO-TI	UN 1155
14.2	UN proper shipping name	
	ADR	DIETHYL ETHER
	IMDG-Code	DIETHYL ETHER
	ICAO-TI	Diethyl ether
14.3	Transport hazard class(es)	
	ADR	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADR	Ι
	IMDG-Code	Ι
	ICAO-TI	Ι
14.5	Environmental hazards	non-environmentally hazardous acc. gerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

to the dan-

according to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ≥99.5 % for synthesis, stabilized

article number: 5920

14.7 Maritime transport in bulk according to IMO instruments The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail information	and inland waterway (ADR/RID/ADN) - Additional
Proper shipping name	DIETHYL ETHER
Particulars in the transport document	UN1155, DIETHYL ETHER, 3, I, (D/E)
Classification code	F1
Danger label(s)	3
*	
Excepted quantities (EQ)	E3
Transport category (TC)	1
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
International Maritime Dangerous Goods (Code (IMDG) - Additional information
Proper shipping name	DIETHYL ETHER
Particulars in the shipper's declaration	UN1155, DIETHYL ETHER, 3, I, -40°C c.c.
Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	-
Excepted quantities (EQ)	E3
Limited quantities (LQ)	0
EmS	F-E, S-D
Stowage category	E
International Civil Aviation Organization (I	CAO-IATA/DGR) - Additional information
Proper shipping name	Diethyl ether
Particulars in the shipper's declaration	UN1155, Diethyl ether, 3, I
Danger label(s)	3
*	
Excepted quantities (EQ)	E3

according to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ≥99.5 % for synthesis, stabilized

article number: 5920

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)						
Name of substance	Name acc. to inventory	CAS No	Restriction	No		
Diethyl ether	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3		
Diethyl ether	flammable / pyrophoric		R40	40		

Legend R3

R40

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in orna-mental lamps and ashtrays,

- tricks and jokes,

games for one or more participants, or any article intended to be used as such, even with ornamental aspects,

Articles not complying with paragraph 1 shall not be placed on the market.
 Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume,

Stan hot be placed on the market in they contain a colouring agent, unless required for inscarreasons, or perturne, or both, if they:
— can be used as fuel in decorative oil lamps for supply to the general public, and
— present an aspiration hazard and are labelled with H304.
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation

(CEN).
5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and pack5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met

(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil

follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp of - or even sucking the wick of lamps - may lead to life-threatening lung damage";
(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
(c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.';
Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the full of the full of the full of the full of the denerative public full of the full of the denerative public full of the full of the denerative public ful

for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,

- artificial snow and frost,

- 'whoopee' cushions,

silly string aerosols,
 imitation excrement,

horns for parties,
decorative flakes and foams,

- artificial cobwebs, - stink bombs.

2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'.

3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).

4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

Seveso Directive

according to Regulation (EC) No. 1907/2006 (REACH)

Diethyl ether ≥99.5 % for synthesis, stabilized



article number: 5920

2012/18/EU (Seveso III)						
No	Dangerous substance/hazard categories	Qualifying quantity plication of lower quirer		Notes		
P5a	flammable liquids (cat. 1)	10	50	49)		

Notation

49)

- Flammable liquids, category 1, or - flammable liquids category 2 or 3 maintained at a temperature above their boiling point, or - other liquids with a flash point \leq 60 °C, maintained at a temperature above their boiling point

Deco-Paint Directive

VOC content	100 % 710 ⁹ / ₁

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	710 ^g /l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer **Register (PRTR)**

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)					
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks	
Diethyl ether	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)		

Legend

Indicative list of the main pollutants A)

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

Name of substance	CAS No	Classification	CN Code	Threshold level
Diethyl ether	60-29-7	Category 3	2909 11 00	

Regulation on substances that deplete the ozone layer (ODS) not listed

according to Regulation (EC) No. 1907/2006 (REACH)

Diethyl ether ≥99.5 % for synthesis, stabilized



article number: 5920

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Diethyl ether	60-29-7	Table II	2909.11

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) Domestic Substances List (DSL) EC Substance Inventory (EINECS, ELINCS, NLP) Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances AIIC CICR CSCL-ENCS DSL ECSI IECSC INSQ KECI Korea Existing Chemicals Inventory NZIOC New Zealand Inventory of Chemicals PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS) REACH Reg. REACH registered substances TCSI TSCA Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 **Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out for this substance.

according to Regulation (EC) No. 1907/2006 (REACH)





article number: **5920**

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Narcotic effects.	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAP. 424	Occupational Health and Safety Authority Act (CAP. 424)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CN Code	Combined Nomenclature
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval

according to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ≥99.5 % for synthesis, stabilized

article number: 5920

Abbr.	Descriptions of used abbreviations
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

according to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ≥99.5 % for synthesis, stabilized

article number: 5920

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapour.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.