



Health	3
Fire	0
Reactivity	0
Personal Protection	

## Safety Data Sheet Nitric acid

### Section 1: Chemical Product and Company Identification

**Product Name:** Nitric acid

**Contact Information:**

**Catalog Codes:** 205,206,207

**Email:** [info@drm-chem.com](mailto:info@drm-chem.com)

**CAS#:** Mixture

**Address:** #7, Afshar javan Alley, Sohrevardi

**RTECS:** Not applicable

St ,Tehran, Iran

**TSCA:** TSCA 8(b) inventory: Water; Nitric acid,

**post code:** 1551818111

**Synonym:** Nitric Acid 55%, 60%, 65%

Tehran Sales: +98 21 88177760

**Chemical Name:** Not applicable

**Order Online:** [Drm-chem.com](http://Drm-chem.com)

**Chemical Formula:** Not applicable

### Section 2: Composition and Information on Ingredients

**Composition:**

Name	CAS #	% by Weight
Water	7732-18-5	35
Nitric acid, fuming	7697-37-2	65

**Toxicological Data on Ingredients:** Nitric acid, fuming: VAPOR (LC50): Acute: 244 ppm 0.5 hours [Rat]. 344 ppm 0.5 hours [Rat].

### Section 3: Hazards Identification

**Potential Acute Health Effects:**

Very hazardous in case of skin contact (corrosive, irritant, permeator), of eye contact (irritant, corrosive), of ingestion, . Slightly hazardous in case of inhalation (lung sensitizer). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Prolonged exposure may result in skin burns and ulcerations. Over-exposure by inhalation may cause respiratory irritation. Severe over-exposure can result in death. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

**Potential Chronic Health Effects:**

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to lungs, mucous membranes, upper respiratory

tract, skin, eyes, teeth. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.

#### Section 4: First Aid Measures

**Eye Contact:**

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.

**Skin Contact:**

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

**Serious Skin Contact:**

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

**Inhalation:**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**Serious Inhalation:**

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. **WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

**Ingestion:**

If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

**Serious Ingestion:** Not available.

#### Section 5: Fire and Explosion Data

**Flammability of the Product:** Non-flammable.

**Auto-Ignition Temperature:** Not applicable.

**Flash Points:** Not applicable.

**Flammable Limits:** Not applicable.

**Products of Combustion:** Not available.

**Fire Hazards in Presence of Various Substances:** of combustible materials

**Explosion Hazards in Presence of Various Substances:**

Explosive in presence of reducing materials, of organic materials, of metals, of alkalis. Non-explosive in presence of open flames and sparks, of shocks.

**Fire Fighting Media and Instructions:** Not applicable.

**Special Remarks on Fire Hazards:**

Flammable in presence of cellulose or other combustible materials. Phosphine, hydrogen sulfide, selenide all ignite when fuming nitric acid is dripped into gas. (Nitric Acid, fuming)

**Special Remarks on Explosion Hazards:**

Reacts explosively with metallic powders, carbides, cyanides, sulfides, alkalies and turpentine. Can react explosively with many reducing agents. Arsine, phosphine, tetraborane all oxidized explosively in presence of nitric acid. Cesium and rubidium

acetylides explode in contact with nitric acid. Explosive reaction with Nitric Acid + Nitrobenzene + water. Detonation with Nitric Acid + 4-Methylcyclohexane. (Nitric acid, fuming)

## Section 6: Accidental Release Measures

### Small Spill:

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. If necessary: Neutralize the residue with a dilute solution of sodium carbonate.

### Large Spill:

Corrosive liquid. Oxidizing material. Poisonous liquid. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Use water spray curtain to divert vapor drift. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Neutralize the residue with a dilute solution of sodium carbonate. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

## Section 7: Handling and Storage

### Precautions:

Keep locked up.. Keep container dry. Keep away from heat. Keep away from sources of ignition. Keep away from combustible material.. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as reducing agents, combustible materials, organic materials, metals, acids, alkalis, moisture. May corrode metallic surfaces. Store in a metallic or coated fiberboard drum using a strong polyethylene inner package.

### Storage:

Keep container tightly closed. Keep container in a cool, well-ventilated area. Separate from acids, alkalies, reducing agents and combustibles. See NFPA 43A, Code for the Storage of Liquid and Solid Oxidizers. Do not store above 23°C (73.4°F).

## Section 8: Exposure Controls/Personal Protection

### Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

### Personal Protection:

Face shield. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves. Boots.

### Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

### Exposure Limits:

TWA: 2 STEL: 4 (ppm) from ACGIH (TLV) [United States] TWA: 2 STEL: 4 from OSHA (PEL) [United States] Consult local authorities for acceptable exposure limits.

## Section 9: Physical and Chemical Properties

**Physical state and appearance:** Liquid.

**Odor:** Acrid. Disagreeable and choking. (Strong.)

**Taste:** Not available.

**Molecular Weight:** Not applicable.

**Color:** Colorless to light yellow.

**pH (1% soln/water):** Acidic.

**Boiling Point:** 121°C (249.8°F)

**Melting Point:** -41.6°C (-42.9°F)

**Critical Temperature:** Not available.

**Specific Gravity:** 1.408 (Water = 1)

**Vapor Pressure:** 6 kPa (@ 20°C)

**Vapor Density:** 2.5 (Air = 1)

**Volatility:** Not available.

**Odor Threshold:** 0.29 ppm

**Water/Oil Dist. Coeff.:** Not available.

**Ionicity (in Water):** Not available.

**Dispersion Properties:** See solubility in water, diethyl ether.

**Solubility:**

Easily soluble in cold water, hot water. Soluble in diethyl ether.

## Section 10: Stability and Reactivity Data

**Stability:** The product is stable.

**Instability Temperature:** Not available.

**Conditions of Instability:** Incompatible materials

**Incompatibility with various substances:**

Highly reactive with alkalis. Reactive with reducing agents, combustible materials, organic materials, metals, acids.

**Corrosivity:**

Extremely corrosive in presence of aluminum, of copper. Non-corrosive in presence of glass, of stainless steel(304), of stainless steel(316), of brass.

**Special Remarks on Reactivity:**

A strong oxidizer. Reacts violently with alcohol, organic material, turpene, charcoal. Violent reaction with Nitric acid + Acetone and Sulfuric acid. Nitric Acid will react with water or steam to produce heat and toxic, corrosive and flammable vapors. (Nitric acid, fuming)

**Special Remarks on Corrosivity:**

In presence of traces of oxides, it attacks all base metals except aluminum and special chromium steels. It will attack some forms of plastics, rubber, and coatings. No corrosive effect on bronze. No corrosivity data for zinc, and steel

**Polymerization:** Will not occur.

## Section 11: Toxicological Information

**Routes of Entry:** Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

**Toxicity to Animals:**

LD50: Not available. LC50: Not available.

**Chronic Effects on Humans:**

Contains material which may cause damage to the following organs: lungs, mucous membranes, upper respiratory tract, skin, eyes, teeth.

**Other Toxic Effects on Humans:**

Extremely hazardous in case of inhalation (lung corrosive). Very hazardous in case of skin contact (corrosive, irritant, permeator), of eye contact (corrosive), of ingestion, .

**Special Remarks on Toxicity to Animals:** LDL - Lowest Published Lethal Dose [Human] - Route: Oral; Dose: 430 mg/kg (Nitric acid, fuming)

**Special Remarks on Chronic Effects on Humans:**

May cause adverse reproductive effects (effects on newborn and fetotoxicity) based on animal data. (Nitric acid, fuming)

**Special Remarks on other Toxic Effects on Humans:**

Acute Potential Health Effects: Skin: Severely irritates skin. Causes skin burns and may cause deep and penetrating ulcers of the skin with a characteristic yellow to brownish discoloration. May be fatal if absorbed through skin. Eyes: Severely irritates eyes. Causes eye burns. May cause irreversible eye injury. Ingestion: May be fatal if swallowed. Causes serious gastrointestinal tract irritation or burns with nausea, vomiting, severe abdominal pain, and possible "coffee grounds" appearance of the vomitus . May cause perforation of the digestive tract. Inhalation: May be fatal if inhaled. Vapor is extremely hazardous. Vapor may cause nitrous gas poisoning. Effects may be delayed. May cause irritation of the mucous membranes and respiratory tract with burning pain in the nose and throat, coughing, sneezing, wheezing, shortness of breath and pulmonary edema. Other symptoms may include nausea, and vomiting. Chronic Potential Health Effects: Repeated inhalation may produce changes in pulmonary function and/or chronic bronchitis. It may also affect behavior (headache, dizziness, drowsiness, muscle contraction or spasticity, weakness, loss of coordinaton, mental confusion), and urinary system (kidney faillure, decreased urinary output after several hours of

## Section 12: Ecological Information

**Ecotoxicity:** Not available.

**BOD5 and COD:** Not available.

**Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

**Toxicity of the Products of Biodegradation:** The products of degradation are less toxic than the product itself.

**Special Remarks on the Products of Biodegradation:** Not available.

## Section 13: Disposal Considerations

**Waste Disposal:**

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

## Section 14: Transport Information

**DOT Classification:** Class 8: Corrosive material

**Identification:** : Nitric acid UNNA: 2031 PG: II

**Special Provisions for Transport:** Marine Pollutant

## Section 15: Other Regulatory Information

**Federal and State Regulations:**

New York release reporting list: Nitric acid, fuming Rhode Island RTK hazardous substances: Nitric acid, fuming Pennsylvania RTK: Nitric acid, fuming Florida: Nitric acid, fuming Minnesota: Nitric acid, fuming Massachusetts RTK: Nitric acid, fuming

New Jersey: Nitric acid, fuming TSCA 8(b) inventory: Water; Nitric acid, fuming SARA 302/304/311/312 extremely hazardous substances: Nitric acid, fuming SARA 313 toxic chemical notification and release reporting: Nitric acid, fuming 65% CERCLA: Hazardous substances.: Nitric acid, fuming: 1000 lbs. (453.6 kg);

**Other Regulations:** OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

**Other Classifications:**

**WHMIS (Canada):**

CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). CLASS D-2A: Material causing other toxic effects (VERY TOXIC). CLASS E: Corrosive liquid.

**DSCL (EEC):**

R8- Contact with combustible material may cause fire. R35- Causes severe burns. S23- Do not breathe gas/fumes/vapour/spray [\*\*\*] S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36- Wear suitable protective clothing. S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

**HMIS (U.S.A.):**

**Health Hazard:** 3

**Fire Hazard:** 0

**Reactivity:** 0

**Personal Protection:**

**National Fire Protection Association (U.S.A.):**

**Health:** 4

**Flammability:** 0

**Reactivity:** 0

**Specific hazard:**

**Protective Equipment:**

Gloves. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Face shield.

## Section 16: Other Information

**References:** Not available.

**Other Special Considerations:** Not available

**Created:** 07/2015

**Last Updated:** 07/2022

*The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Drm-chem.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Drm-chem.com has been advised of the possibility of such damages.*